

For vents from these processes . . .	You must meet the following emissions limits . . . <sup>a</sup>	
	Total hydrocarbon ppm by volume expressed as propane corrected to 4 percent carbon dioxide	Dioxin and furan (dioxins and furans) nanograms/dscm expressed as TEQ corrected to 7 percent O <sub>2</sub>
Reverberatory and electric furnaces that commence construction or reconstruction after May 19, 2011.	12 ppmv .....	0.10 ng/dscm.

<sup>a</sup>There are no standards for dioxins and furans during periods of startup and shutdown.

TABLE 3 TO SUBPART X OF PART 63—TOXIC EQUIVALENCY FACTORS

Dioxin/furan congener	Toxic equivalency factor
2,3,7,8-tetrachlorinated dibenzo-p-dioxin .....	1
1,2,3,7,8-pentachlorinated dibenzo-p-dioxin .....	0.5
1,2,3,4,7,8-hexachlorinated dibenzo-p-dioxin .....	0.1
1,2,3,7,8,9-hexachlorinated dibenzo-p-dioxin .....	0.1
1,2,3,6,7,8-hexachlorinated dibenzo-p-dioxin .....	0.1
1,2,3,4,6,7,8-heptachlorinated dibenzo-p-dioxin .....	0.01
octachlorinated dibenzo-p-dioxin .....	0.001
2,3,7,8-tetrachlorinated dibenzofuran .....	0.1
2,3,4,7,8-pentachlorinated dibenzofuran .....	0.05
1,2,3,7,8-pentachlorinated dibenzofuran .....	0.5
1,2,3,4,7,8-hexachlorinated dibenzofuran .....	0.1
1,2,3,6,7,8-hexachlorinated dibenzofuran .....	0.1
1,2,3,7,8,9-hexachlorinated dibenzofuran .....	0.1

## Subpart Y—National Emission Standards for Marine Tank Vessel Loading Operations

SOURCE: 61 FR 48399, Sept. 19, 1995, unless otherwise noted.

### § 63.560 Applicability and designation of affected source.

(a) *Maximum achievable control technology (MACT) standards.* (1) The provisions of this subpart pertaining to the MACT standards in § 63.562(b) and (d) of this subpart are applicable to existing and new sources with emissions of 10 or 25 tons, as that term is defined in § 63.561, except as specified in paragraph (d) of this section, and are applicable to new sources with emissions less than 10 and 25 tons, as that term is defined in § 63.561, except as specified in paragraph (d) of this section.

(2) Existing sources with emissions less than 10 and 25 tons are not subject to the emissions standards in § 63.562(b) and (d).

(3) The recordkeeping requirements of § 63.567(j)(4) and the emission estimation requirements of § 63.565(l) apply to existing sources with emissions less than 10 and 25 tons.

(4) Existing sources with emissions less than 10 and 25 tons must meet the

submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.

(b) *Reasonably available control technology (RACT) standards.* (1) The provisions of this subpart pertaining to RACT standards in § 63.562(c) and (d) of this subpart are applicable to sources with throughput of 10 M barrels or 200 M barrels, as that term is defined in § 63.561, except as specified in paragraph (d) of this section.

(2) Sources with throughput less than 10 M barrels and 200 M barrels, as that term is defined in § 63.561, are not subject to the emissions standards in § 63.562(c) and (d).

(c) *General Provisions applicability.* Owners or operators of affected sources, as that term is defined in § 63.561, of this subpart must comply with the requirements of subpart A of this part in accordance with the provisions for applicability of subpart A to this subpart in Table 1 of this section.

(d) *Exemptions from MACT and RACT standards.* (1) This subpart does not apply to emissions resulting from marine tank vessel loading operations, as that term is defined in § 63.561, of commodities with vapor pressures less than 10.3 kilopascals (kPa) (1.5 pounds per